



SB-CB



VIDEO

Product Description

4" dia. round fixture support box for use with nonmetallic sheathed cable

Brand: SLIDERBOX®
Catalog #: SB-CB

Width: 4 in.
Depth: 2-3/4 in.
Volume: 25 cu. in.

Type of Installation: Old or New Work
Round Ceiling Box

Carton Quantity: 12
Carton Weight: 3 lb.

UPC: 085339945055
UNSPSC: 39121316
Patents:
U.S. Patent No. 7,855,338

U.S. Patent No. 6,365,831 B1
Country of Origin: United States of America

FEATURES

Machine tapped fixture holes, adjustable mounting plate for additional substrate thickness

APPLICATION

New and old work residential construction 2 HR fire resistive floors and ceilings (50 lbs. fixture support)

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Polycarbonate

MOUNTING

Internal screws with adjustable slider plate for substrates 1/2" to 1 5/32"

ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

Carbon steel fasteners

SUPPORT RATING

50 lbs fixture support