



P-240OW



Product Description

Two gang electrical box for use with nonmetallic sheathed cable

Brand: flexBOX®
Catalog #: P-240OW

Carton Quantity: 24
Carton Weight: 8 lb.

Height: 3-11/16 in.
Width: 4-1/8 in.
Depth: 3-3/8 in.
Volume: 40 cu. in.
Type of Installation: Old Work
Wall Box
Number of Gangs: 2

UPC: 085339249122
UNSPSC: 39121308
Patents:
U.S. Patent No. 6,365,831 B1
Country of Origin: United States of America

FEATURES

Molded-in spline device holes, slot provision for low voltage divider, rectangular exterior for easy cut-in

APPLICATION

Old work residential construction 2 HR fire resistive walls

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Black

ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

MATERIAL

Polycarbonate

MOUNTING

Metal wing brackets/nonmetal ears wall compression