ISSUE DATE: .56 [14.30] - 6.72 [170.69] -3.99 [101.22] .76 [19.41] -> OPTIONAL BACK PANEL SHOWN 0.100 [2.54mm] TH'K- ALUMINUM В 0.075 [1.91mm] TH'K- WHITE STEEL & GALVANNEALED 0.125 [3.18mm] TH'K- FIBERGLASS (4) POLYCARBONATE ÈÉΕΤ 6.50 [165.10] .10 [2.54] 3.50 [88.90] (4) EACH #10-32 BRASS-INSERTS, AND STAINLESS **BACK VIEW** 3.99 [101.32] STEEL FLANGE AND **FEET SCREWS** 7.47 [189.68] 5.20 [131.98] 3.50 [88.90] 6.75 [171.44] STAINLESS STEEL (4)  $\emptyset$ .31 [7.95] **HINGE PIN FRONT VIEW** WITH COVER REMOVED AND BACK PANEL DISPLAYED CLOSED CELL-NEOPRENE STAINLESS STEEL LOCKABLE TWIST LATCH → 4.91 [124.65] <del><</del> → 4.81 [122.24] <del><</del> **GASKET** LOCATED ON CENTER 6.04 [ 153.40 ] .13 [3.30] 4.81 [122.24] 4.25 [107.95] MAT. NO. -(4) EACH #10-32 BRASS INSERTS AND PLATED 4.25 [107.95] **CARBON STEEL SCREWS** 6.26 [158.99] R ALLIED MOULDED PRODUCTS BRYAN, OHIO The Original Fiber Glass Outlet Box AMU Ultraline MATERIAL:
BOX- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER
COVER- COMPRESSION MOLDED FIBERGLASS REINFORCED POLYESTER **CONFIDENTIAL** AMU664TW THIS MATERIAL IS OWNED BY THE ALLIED MOULDED

CLEAR COVER AND WINDOWS- POLYCARBONATE

PRODUCTS COMPANY, IS DISCLOSED IN CONFIDENCE, AND IS NOT TO BE REPRODUCED OR DISTRIBUTED WITHOUT PRIOR WRITTEN PERMISSION FROM ALLIED MOULDED PRODUCTS.