

FLH 010-M**FLH 020-M****FLH 030-M****Mini-Radiant Heaters**

- The FLH Mini series of radiant heaters consists of three versions with heating performance ratings of 10, 20 and 30 Watts.
- The mini-heaters are particularly suitable for use in small housings or for the heating of isolated spots in sensitive areas.



Data	FLH 010-M	FLH 020-M	FLH 030-M	Unit
Part number	17000105017	17000205017	17000305017	
Heating performance	10	20	30	W
Max. surface temperature	203 (95)	239 (115)	284 (140)	°F (°C)
Power consumption	10	20	30	W
Starting current	1.0	1.1	1.2	A
Sytem of protection for intended purpose of use	IP 54			
Weight	85	120	120	g
Rated voltage	230 V AC 50 / 60 Hz			
Functional range	110 - 250 V AC 50 / 60 Hz			
Duty cycle	100%			
Operating temperature range	-40 ... +158 (-40 ... +70)			°F (°C)
Storage temperature range	-40 ... +158 (-40 ... +70)			
Installation orientation	as desired, preferably vertical			
Device construction	aluminum profile, black anodised			
Type of mounting	snap fastening for 35mm profile bars according to EN 60715			
Protection class	II			
Connection	connecting cable 11.8" (300 mm)			
Approvals	UL, cUL, CE			

Accessories	Piece	Part number	Information on page
Thermostat	1	17111000010	
Hygrostat	1	17207000000	

Dimensions

Dimension	FLH 010-M	FLH 020-M / 030-M
	inches (mm)	
X	1.16 (29.5)	1.16 (29.5)
Y	1.77 (45)	1.77 (45)
Z	1.97 (50)	2.95 (75)
L	11.81 (300)	11.81 (300)

